



PROPER ENCLOSURE SOLUTIONS LTD

500
S
E
R
I
E
S

I
N
S
T
R
U
M
E
N
T

E
N
C
I
O
S
U
R
E
S

Standard Specification

Fully weatherproof enclosure in two parts, with stainless steel hinges, propstay(s) and heavy-duty padlockable over-centre fasteners. Fitted with galvanised mild steel baseplate and mounting clamp so suit a 2"NB pipestand. Weatherproof seal provided by neoprene gasket. Also available in lift-off version. Standard colour:- light grey.

| Model | A | B | C | D | E |
|-------|------|-----|-----|----|-----|
| 501 | 345 | 340 | 397 | 64 | 83 |
| 501a | 345 | 420 | 397 | 64 | 83 |
| 501b | 345 | 380 | 397 | 64 | 123 |
| 501c | 345 | 460 | 397 | 64 | 123 |
| 501d | 687 | 445 | 407 | 64 | 83 |
| 501t* | 1030 | 445 | 407 | 64 | 83 |

*Mounting Clamp for Twin Pipestands on 500mm CTRS.

Options

500 Series enclosures can be supplied fitted with any of our full range of accessories covering heating, ventilation, cable/tubing entries, viewing and tagging systems.

500 Series enclosures are designed to accommodate all modern pressure, temperature and DP instruments, in single and multi-instrument installations. The shallow base and deep lid sections give compact size when closed and good all-round access when open, with raised front splitline lending itself to convenient horizontal 'splitline' impulse line entries.

